

WEST[Help](#)[Logout](#)[Main Menu](#) [Search Form](#) [Result Set](#) [Show S Numbers](#) [Edit S Numbers](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#) [Title](#) [Citation](#) [Front](#) [Review](#) [Classification](#) [Date](#) [Reference](#) [Claims](#) [RMD](#)**Document Number 81**

Entry 81 of 179

File: JPAB

Oct 18, 1996

PUB-NO: JP408274812A
DOCUMENT-IDENTIFIER: JP 08274812 A
TITLE: VOICECOMMUNICATION SYSTEM

PUBN-DATE: October 18, 1996

INVENTOR-INFORMATION:

NAME

FUJII, AKIHIRO

FUKUNAGA, SHIGERU

NAKAI, TOSHIHISA

ASSIGNEE-INFORMATION:

NAME

COUNTRY

OKI ELECTRIC IND CO LTD N/A

APPL-NO: JPO7073166

APPL-DATE: March 30, 1995

INT-CL (IPC): H04L 12/56; H04L 12/40

ABSTRACT:

PURPOSE: To make possible efficient voice communication with high-quality reproduced voices with simple communication protocol configuration.

CONSTITUTION: Terminals 1a-1c are connected to a bus type LAN3. These terminals 1a-1c are composed respectively of voice transmission parts 100, voice reception parts 200, CPU and display devices, etc. With this configuration, the system for permitting the efficient communication with high-quality reproduced voices while using under datagram protocols is constructed. When sending a voice to the terminal 1a, the terminal 1b transmits the voice signal of a sound term as a main body packet and transmits an end packet just after the sound term. Further, time information and packet information are added to the headers of these packets in addition to voice data.

COPYRIGHT: (C)1996,JPO

[Main Menu](#) [Search Form](#) [Result Set](#) [Show S Numbers](#) [Edit S Numbers](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#) [Title](#) [Citation](#) [Front](#) [Review](#) [Classification](#) [Date](#) [Reference](#) [Claims](#) [RMD](#)[Help](#)[Logout](#)